

• **PERFORMANCE DATA**

R32 150,000Btu



MODEL		XDSPH450C3
Heating Capacity	BTU	150,000BTU
Power Supply	/	208-240V~/1Ph~60Hz
Circuit Breaker	Amps	50
Advised pool volume	m3	120~200
	Gallon	32,000-53,000
Operating air temperature	°C	-10• 43C (14F-110F)
Performance Condition• Air 27°C(80.6F) /Water 27°C(80F) /Humid. 80%• •		
Heating Capacity	BTU	150,000
COP	/	6.92
Performance Condition: Air 80°F (27°C), Water 80°F (27°C), Humidity 63%		
Heating Capacity	BTU	123,000
COP	/	6.74
Performance Condition: Air 50°F (10°C), Water 80°F (27°C), Humidity 63%		
Heating Capacity	BTU	130,000
COP	/	4.82
Casing type	/	ABC Casing
Fan Quantity	/	1
Fan Power Input	W	390
Fan Speed	RPM	500~900
Fan Direction	/	Up charging
Sound Pressure 1m	dB(A)	55~62
Water Connection	mm	50 (1.96in)
Water Flow Volume	m3/h	15
Net Dimensions L/W/H	mm	1033×1054×820(40.7*41.5*32.3in)
Refrigerant	/	R32
Compressor	Brand	INVERTER